

Programming Paradigms Exercise 6 - Haskell 2

Theodoros Chondrogiannis

2nd Semester 2016/17

1. Write a function `innerprod` that takes two vectors `v` and `w` represented by lists and returns the inner product. The inner product of two vectors is defined as $\vec{v} \circ \vec{w} = v_1 \cdot w_1 + v_2 \cdot w_2 + \dots v_n \cdot w_n$. For example, if `v = [3,5,0,2]` and `w = [2,3,1,4]`, then the product of `v` and `w` is equal to $3 \cdot 2 + 5 \cdot 3 + 0 \cdot 1 + 2 \cdot 4 = 6 + 15 + 0 + 8 = 29$. The input vectors must have equal length. Otherwise the return value must be -1.
2. Implement the sieve of Eratosthenes in Haskell. This algorithm determines all the prime numbers in a range of numbers by removing all the multiples of 2,3,5,7,... from the range. What is left in the range are only prime numbers. For example, for the range [2..20] (1 is not a prime number), we would first remove all multiples of 2 and are left with [2,3,5,7,9,11,13,15,17,19]. In the next step we remove multiples of 3 and are left with [2,3,5,7,11,13,17,19]. Once we reach a number whose first multiple is larger than 20, we stop.
3.
 - (a) Write a function `selectsort` that sorts a list using the selection sort algorithm.
 - (b) Write a function `quicksort` that sorts a list using the quicksort algorithm.
 - (c) Write a function `qs_lo1` which employs the quicksort algorithm, gets a list of lists as an input and returns a list of lists as an output, such that each outputted list is sorted using the values of the last list as sort keys. For example, the input
`[ [0,1,2] , [23,26,30] , [3400,1700,5000] ]`
should result in the output:
`[ [1,0,2] , [26,23,30] , [1700,3400,5000] ]`.
 - (d) Write two functions `qs_lc_tuple.f` and `qs_lc_tuple.l` which employ the quicksort algorithm, get a list of tuples of the form `(Int,Int)` and return the list sorted in ascending order of the first element or the last element respectively.

For example,

```
qs_lc_tuple_f [(5,1),(6,4),(2,8),(4,2)]  
[(2,8),(4,2),(5,1),(6,4)]
```

and

```
qs_lc_tuple_l [(5,1),(6,4),(2,8),(4,2)]  
[(5,1),(4,2),(6,4),(2,8)]
```

You can use the build-in functions: `minimum`, which returns the minimum element of a list, and `delete`, which deletes the first occurrence of an element from a list. In order to use `delete` you have to import the module `Data.List`.