

## 11. XSLT Stylesheets (2)

These exercises are about XSLT stylesheets. You are asked to write a stylesheets to achieve a number of tasks.

Run your stylesheets using Kernow. On the sheet for Lab 9, you can find instructions how to download Kernow, a graphical frontend to the Saxon XQuery/XSLT processor. Kernow is a Java package and can be run under Linux, Windows and Mac OS.

You can develop your stylesheets in the XSLT Sandbox of Kernow. The outermost element of your stylesheets should be of the kind `xsl:stylesheet`, with attributes set as shown below:

```
<xsl:stylesheet version="2.0"
                xmlns:xsl="http://www.w3.org/1999/XSL/Transform">
```

In the lectures, we have introduced XSLT 1.0, because version 2.0 is not yet widely supported. Saxon, however, is a processor for XSLT 2.0 and will return a warning if you declare your stylesheet as of version 1.0.

To tell Kernow that the output should be XML 1.0 and that we would like it properly indented, add as the first element in the stylesheet the following output specification:

```
<xsl:output method="xml"
            version="1.0"
            encoding="iso-8859-1"
            indent="yes"/>
```

The version of Kernow that you download allows you to run 100 queries. Then it will ask you to enter a code in order to proceed. I have the code and will send it to you if you ask me by email.

These exercises are largely similar to the ones for XQuery. This is intentional, since both XQuery and XSLT allow one to specify transformations turning XML documents into other XML or (X)HTML documents.

The exercises allow you to compare the means by which such transformations can be expressed in the two languages.

## Countries

The following are transformations over the `countries.xml` document. Formulate your transformations in such a way that they return the correct result for all possible recipe documents that satisfy `countries.dtd`.

1. Return an element `<countries>` with a list of `<country>` elements, containing in turn elements `<name>` and `<population>`, such that each country of the document appears once. Write the stylesheet so that iteration is achieved by recursive calls to templates.
2. Return a similar list, ordered by `<population>` in descending order. Write the stylesheet so that iteration is expressed by `<xsl:for-each>` elements.
3. Rewrite the preceding stylesheet in such a way that you use dynamic element constructors to construct the new elements.
4. Rewrite the stylesheet from Exercise 2 or 3 in such a way that you create country elements and `name` and `population` attributes and that you use shallow and deep copying wherever possible.
5. Return a list of `<city>` elements, containing the name of the city, such that each city has an attribute `population` and another attribute `country`. The cities are returned according to their population, in descending order. Use iteration by template call.
6. Restructure the document by listing countries according to population, cities within each country according to population, and languages within each country according to percentage, all in descending order.
7. Return an element `<languages>` with a list of `<language>` elements, alphabetically sorted, where each language from the countries documents occurs exactly once. Use the two approaches shown in the lecture.
8. Return an element `<languages>` with a list of `<language>` elements, alphabetically sorted, where each language element contains a list of country elements, such that the language is spoken in the country, together with the number of speakers of the language in that country.  
**Hint:** You may need parameters, named templates, calls to templates, and the formatting function `format-number`. Parameters and named templates are documented on the lecture slides.
9. Create a stylesheet that produces an HTML layout of the countries document. Follow the example of the recipes layout from the lecture.